

APPLICATION:		PRODUCT NAME:	٦ ٩
		WIDESPREAD DECK FAUCET	5
JOB NAME:		SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS	7 660
QUANTITY:	ITEM NO.	MODEL:	<u>-</u> ا ر
		☐ 1899 W/ 12" SWIVEL GOOSENECK SPOUT	



MODEL	DIM "A"	DIM "B"	DIM "C"
1899	8-3/16"	12-5/16"	5-1/2"
	[208.0mm]	[312.7mm]	[139.7mm]
1910	4-7/16"	8-1/16"	3-1/2"
	[112.7mm]	[204.8mm]	[88.9mm]

ROUGH-IN:



(SP) ANSI/A112.18.1M

	WIDESPREAD DECK FAUCET	!			
	SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS				
MODEL:		1			
□ 1899	W/ 12" SWIVEL GOOSENECK SPOUT	ľ			
□ 1910	W/ 6" SWIVEL GOOSENECK SPOUT				
OPTIONS OR MODIFICATIONS:					
☐ SUPPLY LINES (24" OR 36") CIRCLE LENGTH					
☐ ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE					

☐ OTHER **FEATURES**

CONTROL VALVE

* WIDESPREAD DECK ADJUST. FROM 6" TO 24"

☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE

* SWIVELLING SEAT DISK

☐ IN-LINE DUAL CHECK VALVE

□ VANDAL RESISTANT KIT

- * HOT SIDE STEM RIGHT HAND
- * COLD SIDE STEM LEFT HAND
- * STAINLESS STEEL SEAT
- * STAINLESS STEEL SEAT SCREW
- * STAINLESS STEEL HANDLE SCREW

SYSTEM LIMITS

- * TEMP: 40°F MIN. TO 140°F MAX.
- * PRESSURE: 200 PSI MAX. STATIC
- * 2.20 GPM AT 60 PSI

SHIPPING WEIGHT

* 5.0 LBS



TOLL FREE: 800-421-6162 - FAX: 800-832-8238