APPLICATION:		PRODUCT NAME:	ြန
		SINGLE WALL POT FILLER W/SHUT-OFF	SPEC.
JOB NAME:		SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS	2348 F
QUANTITY:	ITEM NO.	MODEL:	REV.A
10-[260. 4-15/16" [125.4mm] 3/4" NPT - FEMALE		OPTIONS OR MODIFICATIONS: SUPPLY LINES (24" OR 36") CIRCLE LENGTH NIPPLES ELBOWS HANDLES (CROSS OR WRIST) CIRCLE STYLE VANDAL RESISTANT KIT OTHER FEATURES * SINGLE WALL * SWIVEL OUTLET * SWIVELLING SEAT DISKS * STAINLESS STEEL SEATS * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS * HOT & COLD INDEX BUTTONS HOSE * 72" LG. HEAT MASTER FDA NITRILE/ARAMID * NSF-51 (100 PSI W.P. @ 300°F) CONSTANT * RENEWABLE END FITTINGS & BUMPER * 360° SWIVEL POT FILLER SPOUT * NONMARRING POT FILLER SPOUT * SHUT-OFF SPOUT * SHUT-OFF SPOUT * 360° SWIVEL ELBOW RECOMMENDED SETTINGS * 110°F AT 80 PSI SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE 200 PSI MAX. STATIC * 29 GPM @ 80 PSI SHIPPING WEIGHT * 15.0 LBS	-
ROUGH-IN:			
	Ø1-3/16" 80.16mm]	F/SHER	

FISHER MANUFACTURING COMPANY
TOLL FREE: 800-421-6162 - FAX: 800-832-8238
information@fisher-mfg.com - www.fisher-mfg.com

ANSI/A112.18.1M

(B)