

MINTA TOUCH
Pull-Down kitchen faucet with
touch technology

MODEL # 31392

GROHE America, Inc | 200 North Gary Avenue, Suite G, Roselle, IL 60172
Phone: +1 (800) 444-7643 | Fax: +1 (800) 225-2778 | us-customerservice@grohe.com

Pure Freude an Wasser

GROHE



ADA

Product Description:

Pull-Down kitchen faucet with touch technology

**Standard Specification:
with Grotherm Micro**

- Single hole installation
 - **Touch: activation of cold water via skin contact**
 - 6 V lithium-battery supply (type CR-P2)
 - **CE approved**
 - Indication of battery status through different pulses of water
 - Safety shut down circuit (when battery nearly empty)
 - Solenoid valve
 - Automatic safety stop after 60 sec. (factory set)
 - Type of protection IP 44
 - **GROHE SilkMove®** ceramic cartridge
 - **GROHE StarLight®** finish
 - **GROHE SuperSteel** Infinity Finish™
 - **SpeedClean®** anti-lime system
 - Swivel Spout
 - Swivel area 360°
 - Adjustable flow rate limiter
 - **Pull-out Dual Spray Control - switches back and forth between regular flow and spray**
 - **Automatic returning**
 - **Integrated non-return valve**
 - **Locking Push Button Control - to switch from regular flow to spray**
 - **Automatic return to aerator**
 - **Stainless Steel Braided Flexible Supplies**
 - **Quick installation system**
 - **Protected against backflow**
 - **Grotherm Micro 34 507 000**
thermostatic scalding protection
 - **GROHE TurboStat®** thermoelement
 - Built-in non-return valve
 - Dirt strainers
- including connection set
- **GROHE StarLight®** finish
 - Max. pressure differential 5:1
 - Min. recommended pressure: 15 psi

Pure Freude an Wasser



GROHE America, Inc | 200 North Gary Avenue, Suite G, Roselle, IL 60172
Phone: +1 (800) 444-7643 | Fax: +1 (800) 225-2778 | us-customerservice@grohe.com

Applicable Codes & Standards:

- Energy Policy Act of 1992
- NSF 61
- ASME A112.18.1/CSA B125.1
- US Federal and State material regulations
- ICC/ANSI A117.1

Color:

- 31392 000 chrome
- 31392 DC0 supersteel